



VENUS V

THE TOOL OF THE TRADE.

Do you really play your sport with the first things you have around?

Leave assemblies and adjustments to the other.

Let us present you our Victrix Venus, the first European rifle designed for Precision Rifle Series® shooting, ready for delivery and in different versions.

Leave the unexpected to your competitors.

 **VICTRIX**
A R M A M E N T S

Destination use

Sporting ideal for dynamic precision long range shooting

Caliber / Twist rate

6 XC (1/7.5)
6,5 x 47 Lapua (1/8)
6,5 x 47 Lapua (1/8.5)
6,5 Creedmoor (1/8)
6,5 Creedmoor (1/8.5)
6 Creedmoor (1/7.5)
.260 Remington (1/8.5)
.308 Winchester (1/11)

Barrel length

24"

Weight

5,62 kg (12.39 lb), with an empty magazine, muzzle brake, barrel length 24" and no scope

Dimension

Overall length: 1170 mm (46.06")
With muzzle brake and barrel length 24"

Base rifle

Lapped match-grade button rifled barrel in AISI 416R, CERAKOTE black matt finish

Buttstock with horizontal and vertical multiple button adjustments and an adjustable insulated cheek piece, equipped with an Anschutz-type rail on the underside

Single feed and double stack 10-round metal magazine

High strength monobloc chassis in light alloy

Light profile forend in light alloy equipped with attachment system for accessories and QD (Quick Detach) attachments, an integrated Anschutz-type rail in the middle and an integrated Arca rail that runs the entire length

Ergonomic and interchangeable zero angle flat top grip for standard AR platform

20 MoA action rail

Victrix ProAngle Venus V detachable muzzle brake featuring 4 forward canted chambers

Short action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machines.

Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock) and two side lugs arranged at an angle of 105-degree lift; equipped with grooves and an ergonomic interchangeable bolt lever

PVD finish on the action and on the bolt

Victrix Sporting Plus adjustable single stage trigger with a two-position safety: standard setting approx. 400 gr (14.11 oz)


Heavy-duty reinforced transport case

User manual and welcome kit

Stock colour

CERAKOTE ceramic polymer firearm coatings available in:
Orobic Blue
Graphite Black

In case of discrepancy between the data contained in the technical specification and what is visible from the photos, the information reported in the data sheet published on the official website shall prevail.

Graphite Black 
Orobic Blue 